

EMC Test Report

Report No.: AGC05443221119EE01

PRODUCT DESIGNATION: Water powered bamboo LCD clock

BRAND NAME : N/A

MODEL NAME : M06865

APPLICANT: MID OCEAN BRANDS B.V

DATE OF ISSUE : Nov. 24, 2022

STANDARD(S) : EN IEC 55014-1:2021 EN IEC 55014-2:2021

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd





Page 2 of 25

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov. 24, 2022	Valid	Initial release







TABLE OF CONTENTS

1 VERIFICATION OF CONFORMITY	4
2 SYSTEM DESCRIPTION	5
3 MEASUREMENT UNCERTAINTY	5
4 PRODUCT INFORMATION	6
5 SUPPORT EQUIPMENT	7
6 TEST FACILITY	8
7 TEST EQUIPMENT LIST	8
8 TEST SUMMARY LIST	9
9 EN IEC 55014-1 RADIATED EMISSION TEST	10
9.1 LIMITS OF RADIATED DISTURBANCES	10
9.2 BLOCK DIAGRAM OF TEST SETUP	10
9.3 PROCEDURE OF RADIATED EMISSION TEST	11
9.4 TEST RESULT OF RADIATED EMISSION TEST	12
10 EN 61000-4-2 ESD IMMUNITY TEST	14
10.1 BLOCK DIAGRAM OF TEST SETUP	14
10.2 TEST PROCEDURE	15
10.3 PERFORMANCE & RESULT	15
11 EN 61000-4-3 RS IMMUNITY TEST	16
11.1 BLOCK DIAGRAM OF TEST SETUP	16
11.2 TEST PROCEDURE	17
11.3 PERFORMANCE & RESULT	17
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	18
APPENDIX B: PHOTOGRAPHS OF EUT	20





1 VERIFICATION OF CONFORMITY

MID OCEAN BRANDS B.V
7/F, Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
MID OCEAN BRANDS B.V
7/F, Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
MID OCEAN BRANDS B.V
7/F, Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
Water powered bamboo LCD clock
N/A
MO6865
Nov. 17, 2022
Nov. 17, 2022 to Nov. 24, 2022
No deviation from the test method.
Normal
Pass

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. for compliance with the requirements set forth in the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Prepared By	Bibo Zhay	
	Bibo Zhang (Project Engineer)	Nov. 24, 2022
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Nov. 24, 2022
Approved By	Forrest ven	
	Forrest Lei (Authorized Officer)	Nov. 24, 2022



Page 5 of 25

2 SYSTEM DESCRIPTION

	TEST MODE DESCRIPTION						
NO.	TEST MODE DESCRIPTION	WORST					
1	Normal work mode	V					
Note: 1. V m	Note: 1. V means EMI worst mode.						

3 MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in measurement" (GUM) published by ISO.

- Uncertainty of Radiated Emission, Uc = ±3.8dB



Page 6 of 25

4 PRODUCT INFORMATION

Housing Type	Plastic and wood
Classification of apparatus	Category III
EUT Input Rating	Powered by brine
Hardware Version	N/A
Software Version	N/A

I/O Port Information (☐Applicable ☐Not Applicable)

I/O Port of EUT					
I/O Port Type Number Cable Description Tested With					



Page 7 of 25

5 SUPPORT EQUIPMENT

Device Type	Manufacturer	Model Name	Serial No.	Data Cable	Power Cable

Note: "-- "means no any support device during testing.



Page 8 of 25

6 TEST FACILITY

Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao 'an District, Shenzhen, Guangdong, China

7 TEST EQUIPMENT LIST

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
Antenna	SCHWARZBECK	VULB9168	494	Jan. 08, 2021	Jan. 07, 2023
Test software	FARA	EZ-EMC	Ver.RA-03A	N/A	N/A

TEST EQUIPMENT OF ESD TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
ESD Simulator	Schaffner	NSG 438	782	Jan. 03, 2022	Jan. 02, 2023

TEST EQUIPMENT OF RS IMMUNITY TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Signal Generator	R&S	E4421B	MY43351603	Mar. 04, 2022	Mar. 03, 2023
Power Sensor	R&S	URV5-Z4	100124	Apr. 26, 2021	Apr. 25, 2023
Power Meter	R&S	NRVD	8323781027	Apr. 26, 2021	Apr. 25, 2023
Power Amplifier	KALMUS	7100LC	04-02/17-06-001	N/A	N/A
Power Amplifier	Milmega	AS0104-55_55	1004793	N/A	N/A
Antenna	SCHWARZBEC K	VULB9168	494	Jan. 08, 2021	Jan. 07, 2023
Power Amplifier	rflight	NTWPA-256010 0	17063183	N/A	N/A
Broadband High Gain Horn Antenna	SCHWARZBEC K	BBHA 9120 J	00073	N/A	N/A




Page 9 of 25

8 TEST SUMMARY LIST

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted emission	EN IEC 55014-1	EN IEC 55014-1	EN IEC 55014-1	N/A
Radiated emission	EN IEC 55014-1	EN IEC 55014-1	EN IEC 55014-1	Pass
Harmonic current emission	EN IEC 61000-3-2	EN IEC 61000-3-2	Class A	N/A
Voltage fluctuations & flicker	EN 61000-3-3	EN 61000-3-3	§5 of EN 61000-3-3	N/A
Electrostatic discharge immunity	EN IEC 55014-2	EN 61000-4-2	± 8.0 kV (Air Discharge) ± 4.0 kV (Contact Discharge) ± 4.0 kV (Indirect Discharge)	Pass
Radiated electromagnetic field immunity	EN IEC 55014-2	EN 61000-4-3	3V/m with 80% AM. 1kHz Modulation.	Pass
Electrical fast transient/burst Immunity	EN IEC 55014-2	EN 61000-4-4	00-4-4 +/- 1kV for Power Supply Lines	
Surge immunity	EN IEC 55014-2	EN 61000-4-5	+/- 1kV (Line to Line) +/- 2kV (Line to Ground)	N/A
Immunity to Conducted Disturbances Induced by RF fields	EN IEC 55014-2	EN 61000-4-6	3V with 80% AM. 1 kHz Modulation for Power Supply Lines	N/A
Voltage dips and short interruptions immunity	EN IEC 55014-2	EN 61000-4-11	PHASE ANGLE 0, 45, 90, 135, 180, 225, 270, 315 degrees	N/A

Note: N/A means not applicable.





9 EN IEC 55014-1 RADIATED EMISSION TEST

9.1 LIMITS OF RADIATED DISTURBANCES

AT 10M DISTANCES

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m Q.P.)
30-230	10	30.00
230-1000	10	37.00


AT 3M DISTANCES

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m Q.P.)
30-230	3	40.00
230-1000	3	47.00

Note: The lower limit shall apply at the transition frequency.

9.2 BLOCK DIAGRAM OF TEST SETUP

System Diagram of Connections between EUT and Simulators





Report No.: AGC05443221119EE01 Page 11 of 25

(1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per EN IEC 55014-1 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 10cm non-conductive covering to insulate the EUT from the ground plane.

- (2) Support equipment, if needed, was placed as per EN IEC 55014-1.
- (3) All I/O cables were positioned to simulate typical actual usage as per EN IEC 55014-1.
- (4) The EUT was turned on.
- (5) The antenna was placed at 3 meter away from the EUT as stated in EN IEC 55014-1. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- (6) The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- (7) The test mode(s) were scanned during the test.


9.3 PROCEDURE OF RADIATED EMISSION TEST

(8) Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented.




9.4 TEST RESULT OF RADIATED EMISSION TEST

Radiated Emission Test at 3m Distance-Horizontal




No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dΒ	Detector
1		121.5485	5.55	21.54	27.09	40.00	-12.91	peak
2		319.9370	5.21	26.49	31.70	47.00	-15.30	peak
3		446.4141	5.74	26.20	31.94	47.00	-15.06	peak
4		614.2142	6.12	26.88	33.00	47.00	-14.00	peak
5		731.9202	7.42	25.67	33.09	47.00	-13.91	peak
6	*	881.4067	5.38	32.19	37.57	47.00	-9.43	peak

RESULT: PASS





Radiated Emission Test at 3m Distance-Vertical



-				D	^	M			
	No.	Μk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
			MHz	dBuV	dΒ	dBuV/m	dB/m	d₿	Detector
	1		53.5052	7.38	17.03	24.41	40.00	-15.59	peak
	2		123.6984	7.16	16.61	23.77	40.00	-16.23	peak
	3		315.4806	10.51	20.44	30.95	47.00	-16.05	peak
	4		444.8514	5.86	23.88	29.74	47.00	-17.26	peak
	5		696.8567	8.20	29.72	37.92	47.00	-9.08	peak
	6	*	1000.000	6.48	33.00	39.48	47.00	-7.52	peak


RESULT: PASS

Note:

Level(dBuV/m)=Reading(dBuV)+Factor(dB/m)

Factor(dB/m)=Antenna Factor(dB/m)+Cable loss(dB)+Attenuation(dB)for Attenuator

Over= Measurement- Limit






10 EN 61000-4-2 ESD IMMUNITY TEST

ELECTROSTATIC DISCHARGE (ESD) IMMUNITY TEST

Port	Enclosure
Basic Standard	EN 61000-4-2
Test Level	± 8.0 kV (Air Discharge) ± 4.0 kV (Contact Discharge) ± 4.0 kV (Indirect Discharge)
Standard require	В
Temperature	22°C
Humidity	47% RH

10.1 BLOCK DIAGRAM OF TEST SETUP

(The 470 k ohm resistors are installed per standard requirement)



Ground Reference Plane₽



Page 15 of 25

10.2 TEST PROCEDURE

The EUT was located 0.1 m minimum from all side of the HCP.

The support units were located 1 m minimum away from the EUT.

EUT worked with resistance load, and make sure EUT worked normally.

Actives the communication function if the EUT with such port(s).

As per the requirement of EN IEC 55014-2: Contact discharge is the preferred test method. 20 discharges (10 with positive and 10 negative polarity) shall be applied on each accessible metal part of the enclosure. In case of a non-conductive enclosure, discharges shall be applied on the horizontal or vertical coupling planes as specified in EN 61000-4-2.

Air discharges shall be used where contact discharges cannot be applied.

The following test condition was followed during the tests.

Note: As per the A2 to EN 61000-4-2, a bleed resistor cable is connected between the EUT and HCP during the test.

The electrostatic discharges were applied as follows:

Amount of Discharges	Voltage	Coupling	Result
Mini 20 /Point	±4kV	Contact Discharge	Α
Mini 20 /Point	±4kV	Indirect Discharge HCP (Front)	Α
Mini 20 /Point	±4kV	Indirect Discharge HCP (Back)	Α
Mini 20 /Point	±4kV	Indirect Discharge HCP (Left)	Α
Mini 20 /Point	±4kV	Indirect Discharge HCP (Right)	Α
Mini 20 /Point	±4kV	Indirect Discharge VCP (Front)	Α
Mini 20 /Point	±4kV	Indirect Discharge VCP (Back)	Α
Mini 20 /Point	±4kV	Indirect Discharge VCP (Left)	Α
Mini 20 /Point	±4kV	Indirect Discharge VCP (Right)	Α
Mini 20 /Point	±8kV	Air Discharge	Α

10.3 PERFORMANCE & RESULT

Criteria A:	The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
Criteria B:	The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
Criteria C:	Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

⊠ PASS	□FAIL




11 EN 61000-4-3 RS IMMUNITY TEST

RADIATED ELECTROMAGNETIC FIELD IMMUNITY TEST

Port	Enclosure	
Basic Standard	EN 61000-4-3	
Test Level:	3V/m with 80% AM. 1kHz Modulation.	
Standard require	A	
Temperature	20°C	
Humidity	50% RH	

11.1 BLOCK DIAGRAM OF TEST SETUP





Page 17 of 25

11.2 TEST PROCEDURE

The EUT was located at the edge of supporting table keep 3 meter away from transmitting antenna, it just the calibrated square area of field uniformity. The support units were located outside of the uniformity area, but the cable(s) connected with EUT were exposed to the calibrated field as per EN 61000-4-3.

EUT worked with resistance load, and make sure EUT worked normally.

Setting the testing parameters of RS test software per EN 61000-4-3.

Performing the test at each side of with specified level (3V/m) at 1% steps and test frequency from 80MHz to 1000MHz

Recording the test result in following table.

EN 61000-4-3 Final test conditions:

Test level: 3V/m

Steps: 1 % of fundamental

Dwell Time: 3 sec

Range (MHz)	Field	Modulation	Polarity	Position	Test Performance	Result (Criteria meet)
80-1000	3V/m	AM	Н	Front	No function loss	Α
80-1000	3V/m	AM	Н	Left	No function loss	А
80-1000	3V/m	AM	Н	Back	No function loss	А
80-1000	3V/m	AM	Н	Right	No function loss	А
80-1000	3V/m	AM	V	Front	No function loss	А
80-1000	3V/m	AM	V	Left	No function loss	А
80-1000	3V/m	AM	V	Back	No function loss	А
80-1000	3V/m	AM	V	Right	No function loss	А

11.3 PERFORMANCE & RESULT

Criteria A:	The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
Criteria B:	The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
Criteria C:	Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

|--|



APPENDIX A: PHOTOGRAPHS OF TEST SETUP

EN IEC 55014-1 RADIATED EMISSION TEST SETUP




EN 61000-4-2 ESD IMMUNITY TEST SETUP




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/














APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT




BOTTOM VIEW OF EUT






FRONT VIEW OF EUT



BACK VIEW OF EUT




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



LEFT VIEW OF EUT




RIGHT VIEW OF EUT






OPEN VIEW OF EUT-1



OPEN VIEW OF EUT-2






OPEN VIEW OF EUT-3




INTERNAL VIEW OF EUT-1






INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd. (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.